

The FILBO connecting joint is designed and manufactured in according to the international standard norms:

- ISO 3458
- ISO 3459
- ISO 3501
- ISO 3503
- ISO 14236
- DIN 8076-3
- KIWA BRLK 534-01
- UNI 9561
- UNI 9562


The connecting parts of the body with the PE pipes are designed in according to the international standard norms:

- ISO DIS 3607
- DIN 8072
- DIN 8074
- UNI 7611
- UNI 7990

Male and female threaded adaptors are designed in according to the international standard norms:

- ISO 7
- UNISO 7-1
- BS 21

d	Z <sub>min.</sub>	H	L	Z' <sub>min.</sub>	H'	L'	E	g
		Tolerance	Tolerance	Tolerance	Tolerance	Tolerance	Tolerance	
20	28	+3 mm	144 +6 mm	14	+3 mm	72 +3 mm	47 +0.3 mm	100
25	32	+3 mm	166 +6 mm	16	+3 mm	83 +3 mm	54 +0.3 mm	160
32	40	+3 mm	194 +6 mm	20	+3 mm	97 +3 mm	66 +0.3 mm	260
40	54	+5 mm	246 +10 mm	27	+5 mm	123 +5 mm	83 +0.5 mm	560
50	66	+5 mm	286 +10 mm	33	+5 mm	143 +5 mm	98 +0.5 mm	860
63	76	+5 mm	324 +10 mm	38	+5 mm	162 +5 mm	116 +0.5 mm	1210
75								
90								
110								

		DENOMINAZIONE Tee Data Sheet. FISA TEU RAPID PE	
Designer	6, Tsar Ivan Shishman Str. Varna – Bulgaria	Raw Material	Drawing N°
SCALA	Date	Injection Machine	DSH 0007
//	05.06.2007		